

# BETON TROWEL

CONCRETE FINISHING  
& COMPACTION



## CONCRETE VIBRATOR HUMDINGER

Humdinger electric hand held flex drive concrete vibrators.

- Powerful lightweight power unit with robust motor protection
- Flexible shafts from 1m to 6m
- Head diameters from 25mm to 58mm
- Double insulated 2,3 kW motors, 115V & 230V
- Humdinger power unit and shafts available with Wacker or others coupling options for compatible fleet integration on request



### SPECIFICATIONS:

Model		Voltage	kW	Hz	Motor Speed	Weight
HVU110	Humdinger Electric Power Unit	115V	2,3	50/60	18.000	5,5Kg
HVU220	Humdinger Electric Power Unit	230V	2,3	50/60	18.000	5,5Kg

# BETON TROWEL

## CONCRETE FINISHING & COMPACTION



### SPECIFICATIONS:

Model	Head Diameter	Length	Weight (Kg)	Frequency (HZ)	Amplitude (MM)
HDV28/1	28mm	1m	5,50	280	1,40
HDV28/2	28mm	2m	6,10	280	1,40
HDV28/3	28mm	3m	6,80	280	1,40
HDV28/6	28mm	6m	9,40	280	1,40
HDV38/1	38mm	1m	4,96	270	1,54
HDV38/2	38mm	2m	6,26	270	1,54
HDV38/3	38mm	3m	7,56	270	1,54
HDV38/4	38mm	4m	8,86	270	1,54
HDV38/5	38mm	5m	10,36	270	1,54
HDV38/6	38mm	6m	11,86	270	1,54
HDV48/2	48 mm	2m	7.20	260	1.62
HDV48/3	48mm	3m	8,90	260	1,62
HDV48/4	48mm	4m	10,20	260	1,62
HDV48/5	48mm	5m	11,70	260	1,62
HDV58/4	58mm	4m	11.20	250	1.64
HDV58/5	58mm	5m	12,50	250	1,64

